




































	FEATURE	MAX TEMP. FOR CLEAN REMOVAL	STRENGTH	CONFORMABILITY	MARKET
<b>XT</b> <b>PREMIUM PERFORMANCE</b> 	Improved Solvent Resistance	 325°F	 Best	 Extreme	
<b>PG21</b> <b>PREMIUM GRADE</b> 	Improved Temperature Range	 325°F	 Best		
<b>OM</b> <b>PREMIUM GRADE</b> 	High Temperature Range & Smooth Backing	 250°F	 Better		
<b>AM</b> <b>MEDIUM GRADE</b> 	Improved Conformability	 225°F	 Better		
<b>GT</b> <b>INDUSTRIAL GRADE</b> 	Transparent & Clean One-Piece Removal	 225°F	 Better		
<b>SG</b> <b>MEDIUM GRADE</b> 	High Tack	 180°F	 Good		
<b>PM</b> <b>PRODUCTION MASKING</b> 	Value Tape	 180°F	 Good	 Limited	



**PREMIUM SOLVENT RESISTANCY**



- Enhanced backing to ensure superior resistance to solvents
- Superior adhesion to a variety of surfaces
- Resists paint-bleed through



**HIGH TEMPERATURE**



- Fine structured crepe backing sets the standard for sharp paint lines
- Resists paint-bleed through
- Specifically designed adhesive formula to ensure superior adhesion to a variety of surfaces
- High temperature resistances with 3-day UV properties



**UV RESISTANT**



- Exceptional conformability
- Excellent adhesion to backing to provide a secure bond and to prevent lifting and overspray
- Removes cleanly and provides a clean crisp paint line
- 3-day UV resistance



**HIGH CONFORMABILITY**



- Excellent conformability to a variety of surfaces
- Enhanced vibrant aqua backing for high visibility of masked surfaces
- Resists paint flaking and wet sanding



**TRANSPARENT, ONE-PIECE CLEAN REMOVAL**



- Transparent backing to ensure all critical areas are protected
- Strong backing to ensure one-piece clean removal
- Specially formulated to provide a secure bond and to prevent lifting and overspray
- Easy and consistent unwinds to enhance the application process



**HIGH TACK**



- Smooth unwinds for easy of application
- Great holding power with clean removal from a variety of surfaces



**VALUE**



- All-Purpose product for non-critical applications