



INDUSTRIAL GRADE AUTOMOTIVE REFINISHING TAPE

GT is the most versatile of the American® brand portfolio of masking tape for use within the automotive refinishing market. GT was specifically formulated to provide a secure bond to a multitude of surfaces while preventing lift or overspray while painting. The flexible green backing ensures conformable performance around any surface with ease. GT is capable of withstanding temperatures up to 225°F (107°C) for one hour with clean removal. For the best finish, get the best start with American Brand GT!

FEATURES & BENEFITS

- Flexible backing for excellent conformability and ease of application
- Specialized adhesive platform that ensures clean, one-piece, removal
- Excellent wet sanding properties
- Low profile light green backing for superior visibility of masked areas
- Heightened bonding to backing for increased shingling performance



CONFORMABLE



HAND TEARABLE



STRONG HOLD



REMOVES CLEANLY



©2019 Intertape Polymer Group® • GT SS • 100319



888-898-7834 | itape.com



PRODUCT ATTRIBUTES

PRODUCT STYLE	BACKING	ADHESIVE	TOTAL THICKNESS	TENSILE STRENGTH	ADHESION TO STEEL	ELONGATION	TEMPERATURE RESISTANCE
			mils	lb/in of width	oz/in of width	% at break	
GT	Crepe Paper	Natural / Synthetic Rubber	5.8	22	35	9	225°F (107°C)

RESOURCE NUMBER	SIZE	ROLLS PER CASE
GT1855	18mm x 54.8m	48 rolls
GT2455	24mm x 54.8m	36 rolls
GT3655	36mm x 54.8m	24 rolls
GT4855	48mm x 54.8m	24 rolls



PRODUCT APPLICATIONS

- Paint masking requiring adhesion to and removal from a variety of surfaces
- Wet sanding



MARKETS

- Automotive
- Truck
- Bus
- RV
- Marine



For more info
visit itape.com/american

