

Supreme 1

EXPORT GRADE POLYPROPYLENE LUMBER WRAP

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

A high strength, lightweight coated fabric consisting of a reinforcing polypropylene scrim coated with polypropylene on both sides. This product is designed for effective packaging of lumber while in storage and transit.

FABRIC SPECIFICATIONS

Color: White/Black, White/Beige, or other colored coatings available
Weight: 100 g/m² (2.95 oz/yd²)*

ROLL SPECIFICATIONS

Cores: 3 inch I.D., 4 inch I.D. or 5 inch I.D. available
Width: Up to 136 inches (-0, +0.5") as ordered
Length: Up to 1800 yds/roll

These values are typical data and are not intended as limiting specifications.

* Subject to change without prior notification



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Technical Service (Canada): 800.565.4533

Technical Service (US): 800.565.1450

www.itape.com | info@itape.com

PERFORMANCE PROPERTIES

The following data are typical values based on ASTM standard tests. These data should not be considered specification.

Grab Tensile (N) Warp 100 lb (444)/ Weft 90 lb (400)
ASTM D5034

Tongue Tear (N) Warp 35 lb (155)/ Weft 35 lb (155)
ASTM D2261

Trapezoidal Tear (N) Warp 35 lb (155)/ Weft 35 lb (155)
ASTM D4533

Mullen Burst 130 psi (896 kPa)
ASTM D3786

Pliability - 40° C or - 40° F

Outdoor Weathering >80% strength retained after 6 months outdoor exposure

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 6/14

NovaWrap™
BRAND