

FM35

HIGH TEMP FINE LINE SPECIALTY MASKING TAPE

DESCRIPTION

FM35 "fine line" masking tape uses thermally stabilized PVC backing with a rubber-based, pressure-sensitive adhesive. This tape is designed to offer a high degree of conformability, is waterproof, and solvent-resistant. Operating temperature range of 40°F to 280°F (4.4°C to 138°C).

PRODUCT APPLICATIONS

Masking color separations on plastic (TPO and RIM) automotive fascia, trim and finished metals in high temp OEM bake cycles, aircraft paint operations, clean room paint operations.

STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to one (1) year from the date of shipment. Jumbo rolls have the same expected shelf life, but it is recommended that they are converted within six (6) months of date of shipment.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 05/24

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	PVC
Adhesive	Natural Rubber
Tensile Strength (lbs/in of width)	15 (65.6 N/25mm)
Adhesion to Steel (oz/in of width)	23 (6.3 N/25mm)
Elongation (% at break)	150
Total Thickness (mils)	5.4 (0.14mm)
Color	Orange

