

PG48

HIGH TEMP PREMIUM PAPER MASKING TAPE

DESCRIPTION

A beige, high temperature, fine structured, crepe paper masking tape with a pressure-sensitive natural rubber/resin adhesive and a non-printable release coat. Designed for clean removal from a variety of surfaces after exposure to oven temperatures up to 325°F (163°C) for 30 minutes (times and temperatures are determined by surface). Easy, consistent unwind for dispensing of wide width. Performs well in wet strip applications. Its easy handling, smooth crepe backing exhibits high strength, excellent conformability to irregular surfaces and exceptional cornering. Provides both resistance to paint flaking and a clean, well defined paint line.

PRODUCT APPLICATION

Automotive, truck, bus and marine paint masking. Recommended hot to warm removal, but can be removed cold.

STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to one (1) year from the date of shipment. Jumbo rolls have the same expected shelf life, but it is recommended that they are converted within six (6) months of date of shipment.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/14

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Fine Crepe Paper
Adhesive	Natural Rubber
Adhesion to Steel (oz/in of width)	29 (7.9 N/25mm)
Tensile Strength (lbs/in of width)	27 (118 N/25mm)
Elongation (% at break)	10
Total Thickness (mils)	7.7 (0.196mm)
Quick Stick (oz/in of width)	
To Kraft	5.5 (1.5 N/25mm)
To Steel	27 (7.4 N/25mm)
Color	Beige

