

T226

SINGLE LINER HIGH TACK BLASTLITE

DESCRIPTION

IPG's answer to vinyl. Specially formulated rubber provides impact resistance and natural flexibility allowing T226 to conform tightly around curves and uneven surfaces. High-tack acrylic adhesive bonds quickly to clean surfaces. Uniform thickness, high quality, conformable, long-lasting, and easy to use. Release-treated paper liner permits easy tear by hand. Un-punched/friction fed. Can also be cut by knife for precise fit. Unlike vinyl, T226 does not contain PVC and can be safely cut using laser method.

PRODUCT APPLICATION

Superior surface protection and seal. Especially for use on raw wood, unprimed HDU, brick or unglazed tile.

STANDARD SIZES

15" x 10 yds
20" x 10 yds
25" x 10 yds
30" x 10 yds
Also available in slit goods

STORAGE & SHELF LIFE

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/22

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	High Tack / Acrylic
Total Thickness (mil) PSTC-133	27 (0.69 mm)
Tensile Strength (lbs/in) PSTC-131	4.5 (19.71 N/25mm)
180° Adhesion to Steel (oz/in) PSTC-101	42.5 (11.63 N/25mm)
Elongation (% at break) PSTC-131	400
Punch	Unpunched, Hand Cut
Liner Color	White



ANCHOR
brand stencil products