

ProMask Blue[®]
with Bloc-it[™] Clean Line Technology
14 DAY UV RESISTANT
SPECIALTY PAPER

INTERTAPE POLYMER GROUP[®]
TECHNICAL DATA SHEET

DESCRIPTION

Blue fine crepe paper masking tape with a specially formulated pressure-sensitive synthetic rubber adhesive designed for exposure to sunlight up to fourteen days. Featuring IPG's Bloc-it[™] Clean Line Technology. This advanced formula is a proprietary edge treatment that delivers clean, crisp paint lines. Exhibits easy, clean removal from most surfaces. Excellent conformability as well as smooth backing for superior paint lines and reduced fingertip abrasion. Consistent, easy unwind and resistant to humidity and paint bleed-through. Also has secure adhesion and is stain resistant.

PRODUCT APPLICATION

Wherever masking is exposed to weather / out-of-doors conditions, interior masking of windows (where adhesive will be directly exposed to sunlight). Protective, compatible for use on lacquer or polyurethane-coated surfaces, unfinished wood, wallpaper, or new, unpainted, or freshly painted wallboard.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
 Customer Service: 800.IPG.8273 | 800.474.8273
 Tape Technical Service: 877.447.4832
 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 5/13

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Fine Crepe Paper
Adhesive	Synthetic Rubber
Adhesion to Steel (oz/in of width)	26 (7 N/25mm)
Tensile Strength (lbs/in of width)	23 (101 N/25mm)
Elongation (% at break)	11
Total Thickness (mils)	5.5 (0.14mm)
Quick Stick (oz/in of width)	
To Kraft	4 (1.1 N/25mm)
To Steel	12 (3.3 N/25mm)
Color	Blue

