FR55W

PE 3.7 OZ MINE VENTILATION

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

A light-weight, flame-retardant, recyclable, polyethylene fabric suitable for construction sheeting and mine duct applications.

FABRIC SPECIFICATIONS

Weave: Woven clear HDPE scrim Coating: 1.6 mil average both sides

(37 g/m² average per side)

Color: Pale yellow (natural FR)
Weight: 3.7 oz/yd² (125 g/m²) +/- 5 %
Thickness: 5.5 mil (0.14mm) +/- 10%

ROLL SPECIFICATIONS

Cores: 4 inch I.D. or 5 inch I.D.

available

Width: Up to 144 inches (-0, +0.5)

as ordered

Length: Minimum 500 yds/roll;

up to 1000 yds/roll

These values are typical data and are not intended as limiting specifications.

PERFORMANCE PROPERTIES

The following data are typical values based on ASTM standard tests. This data should not be considered specification.

Grab Tensile Warp 65 lb 288 N / Weft 60 lb 266 N ASTM D5034

7.0 TW 20004

Strip Tensile (N/5cm) Warp 40 lb/in (355) / Weft 35 lb/in 310)
ASTM D5035

Tongue Tear Warp 20 lb 90 N / Weft 22 lb 100 N ASTM D2261

Trapezoidal Tear Warp 25 lb 111 N / Weft 20 lb 90 N

ASTM D4533

Mullen Burst 120 psi / 826 kPa ASTM D3786

Flame Retardancy NFPA 701, MSHA 07-BA110003

UV Weathering Not recommended for long-term

outdoor exposure



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.565.2000 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 06/14

