

100e

RECYCLED KRAFT PAPER CARTON SEALING TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

An aggressive pressure-sensitive kraft tape with an adhesive that has been specifically formulated to offer a strong and secure seal on a variety of cartons.

Excellent process performance, whether manually or automatically applied. Superior adhesion properties, quick tack, and easy unwind to ensure consistent, reliable sealing.

PRODUCT APPLICATION

Carton sealing and packaging.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	FSC™ Certified 100% Recycled Kraft Paper
Adhesive	Synthetic Rubber
Adhesion to Steel (oz/in of width) ASTM D3330	72 (20N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	23 (105N/25MM)
Elongation (% at break) PSTC-131	4
Total Thickness (mils) PSTC-133	4.7 (0.12mm)
Temperature Resistance	-10°F ~ + 140°F (-23°C ~ + 60°C)
Application Temperature	59°F ~ + 113°F (15°C ~ + 45°C)
Color	Brown



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/23



The mark of
responsible forestry