

# AT

## AMERICAN® PREMIUM DOUBLE-SIDED ACRYLIC FOAM ATTACHMENT TAPE

### DESCRIPTION

High performance, double-sided acrylic foam tape designed for bonding larger moldings and accessories. Provides instant pressure sensitive bonding and excellent cold temperature adhesion. Will not absorb moisture, conforms to uneven surfaces, and resists stress. Repositionable for accurate alignment without damaging paint.

### PRODUCT APPLICATION

High strength acrylic adhesive provides superior adhesion to various types of plastics, metals, glass, wood, and painted vehicle surfaces. Use in attaching automotive body side moldings, garnish moldings, rocker panel moldings, interior trim panels, door edges, claddings, emblems, fascia rub strips, pillar covers and other accessories. Ideal surface should be at least 60°F (16°C). Use AT Promoter to achieve maximum adhesion on plastic parts. Packaged in a clamshell case for everyday clean storage.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 04/24

# INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Closed Cell Acrylic Foam
<b>Adhesive</b>	Acrylic
<b>Foam Thickness (in)</b>	0.45 (1.1 mm)
<b>180° Adhesion (oz/in of width) ASTM D3330</b>	170.23 (46.5 N/25mm)
<b>Heat Resistance</b>	302°F (150°C) Short term 199.4°F (93°C) Long term
<b>Tape Color</b>	Grey, Black
<b>Liner</b>	Red Film

