

# Ultra Sheeting

## PLASTIC SHEETING FILM

# IPG®

## TECHNICAL DATA SHEET

### DESCRIPTION

A high performance, tear-resistant, and easily workable plastic sheeting film. This transparent, high density plastic film clings to substrates to provide surface protection and can help maintain a clean work environment.

### PRODUCT APPLICATION

Used during repairs, this product protects vehicles from overspray and other potential contaminants.

### STORAGE & SHELF LIFE

Shelf life is nine (9) months from date of manufacture.

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Gauge</b>	0.375 mil
<b>Backing</b>	Polyethylene sheeting/film
<b>Tensile</b> D882	2000 psi (TD) 4000 psi (MD)
<b>Elongation</b> D882	250% (TD) 1500% (MD)
<b>Tear</b> D1922	68g (TD) 3.5g (MD)
<b>Color</b>	Semi-Opaque Natural



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/25

