



INDUSTRIAL GRADE TAPE

GM is a cost-effective industrial grade masking tape specifically designed for industrial and automotive paint masking. GM was specifically formulated to provide a secure bond to a multitude of surfaces while preventing lift or overspray while painting. The flexible green backing ensures conformable performance around any surface with ease. GM is capable of withstanding temperatures up to 200°F (93°C) for 30 minutes with clean removal.



FEATURES & BENEFITS


- Flexible backing for excellent conformability and ease of application
- Specialized adhesive platform that ensures clean, one-piece, removal
- Excellent wet sanding properties
- Low profile light green backing for superior visibility of masked areas
- Heightened bonding to backing for increased shingling performance



CONFORMABLE



HAND
TEARABLE



STRONG
HOLD



REMOVES
CLEANLY



888-898-7834 | itape.com



PRODUCT ATTRIBUTES

PRODUCT STYLE	BACKING	ADHESIVE	TOTAL THICKNESS	TENSILE STRENGTH	ADHESION TO STEEL	ELONGATION	TEMPERATURE RESISTANCE
			mils	lb/in of width	oz/in of width	% at break	
GM	Crepe Paper	Natural rubber/Resin	5.3	24	30	7	200°F (93°C) for 30 min.

RESOURCE NUMBER	SIZE	ROLLS PER CASE
GM1855	18mm x 54.8m	48 rolls
GM2455	24mm x 54.8m	36 rolls
GM3655	36mm x 54.8m	24 rolls
GM4855	48mm x 54.8m	24 rolls



PRODUCT APPLICATIONS

- Paint masking requiring adhesion to and removal from a variety of surfaces
- Wet sanding

MARKETS

- Automotive
- Truck
- Bus
- RV
- Marine
- General Manufacturing
- Industrial



Scan for more info or visit itape.com/american

