



# PESP

## POLYETHYLENE SURFACE PROTECTION FILM TAPE

IPG®'s versatile surface protection tape features a durable polyethylene film with a synthetic natural rubber adhesive, ensuring surfaces are safeguarded from damage. Ideal for use in the marine, automotive, and appliance industries, this tape offers strong adhesion to complete tasks effectively. It can be cleanly removed within 30 days without leaving any residue and provides up to 30 days of UV protection.



### FEATURES & BENEFITS




Moisture resistant



Conformable



UV resistance up to 30 days



Removes cleanly & leaves no residue behind



Easy to unwind



Bonds well to a variety of surfaces



## PRODUCT ATTRIBUTES

STYLE	BACKING	ADHESIVE	THICKNESS	ADHESION TO STEEL	TENSILE STRENGTH	ELONGATION	APPLICATION TEMP RANGE	OPERATING TEMP RANGE	COLOR
			mils (mm)	oz/in (N/25mm)	lbs/in (N/25mm)	%			
PESP	PE film	Synthetic Rubber	5.5 (0.140)	30 (8.2)	25 (110)	45	+45°F to +150°F (+7°C ~ +65°C)	+20°F ~ +200°F (-7°C ~ +93°C)	White

## PRODUCT APPLICATIONS

- Marine, Aerospace & Appliance
- Glass (Auto, Commercial and Residential)
- Stainless
- Marble & Granite
- Automotive, Truck, Bus, RV (OEM for Interior applications. Doors, Consoles, Instrument Panels, Seats, Steering Wheels, Carpet, Door panels etc.)

## MARKETS

- Industrial
- Marine
- Aerospace
- Appliances
- Automotive
- Transportation



Scan for more info or visit [itape.com/petape](http://itape.com/petape)

