

99428

HIGH TEMP PREMIUM PAPER MASKING TAPE

DESCRIPTION

99428 is an orange, high quality, smooth, crepe paper masking tape with a natural rubber adhesive. Good quick-stick and holding properties for the composites industries. Smooth-to-the-touch, straight, clean paint-break line, highly conformable and flexible, tear resistant, moisture and solvent resistant, UV resistant for three (3) days, and can be exposed to oven temperature up to 250°F (121°C) up to 30 minutes. Stain and transfer resistant, controlled unwind, and good adhesion to backing when layered.

PRODUCT APPLICATION

Designed for masking fiberglass molds (gel-coating) and composites where either semi-permanent or paste wax release agents. For marine and other OEM (bus, truck, RV, automotive) paint applications.

STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to one (1) year from the date of shipment. Jumbo rolls have the same expected shelf life, but it is recommended that they are converted within six (6) months of date of shipment.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warranties or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/25

IPG®

TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

| | |
|---|-------------------------|
| Backing | Fine Crepe Paper |
| Adhesive | Natural Rubber/Resin |
| Adhesion to Steel (oz/in of width) PSTC-101 | 27 (7.4 N/25mm) |
| Quick Stick to Kraft (oz/in of width) | 8 (2.2 N/25mm) |
| Tensile Strength (lbs/in of width) PSTC-131 | 23 (101 N/25mm) |
| Elongation (% at break) PSTC-131 | 12 |
| Total Thickness (mils) PSTC-133 | 7.1 (0.18mm) |
| Color | Orange |

